12051 Rivera Road, Santa Fe Springs, CA 90670 FAX 562-698-7029 Phone 562-945-7578

PISTON CLEARANCES

| PRO-X PISTONS | Personal Watercraft Applications Piston-to-Wall Clearances |
|---------------|--|
| Piston Size | Recommended Clearance (size in thousandths) |
| 68 to 70mm | .003" to .0035" |
| 75 to 78mm | .0038" to .0043" |
| 80 to 82mm | .004" to .0045" |

| PRO-X PISTONS | Motorcycle - ATV Applications Piston-to-Wall Clearances | |
|---------------|---|--|
| Piston Size | Recommended Clearance (size in thousandths) | |
| 47 to 52mm | .0018" to .0023" | |
| 54 to 57mm | .0023" to .0026" | |
| 65 to 72mm | .0024" to .0028" | |
| 89 to 91mm | .0032" to .0036" | |

Wiseco PISTONS
Wiseco recommended piston to cylinder wall clearances for Air Cooled and Water Cooled 2-Cycle Engines:

| BORE SIZE | CLEARANCES | |
|--|------------|--|
| Under 52mm (2.047*) | | |
| 52mm (2.047") to 60mm (2.362") | (.05mm) | |
| 60mm (2.362") to 73mm (2.874") | | |
| 73mm (2.874") and up003" (.075mm) | | |
| Piston clearances are pre-set for all plated cylinder bores. | | |